OXDALE PRODUCTS



AGRICULTURAL, FORESTRY & GRASSLAND MACHINERY



BROCHURE 2021

Oxdale Products Ltd 20-21 Foxwood Road, Off Sheepbridge Lane, Chesterfield, Derbyshire S41 9RF

OXDALE PRODUCTS

Introduction





Oxdale Products was founded in 2008 in Chesterfield, Derbyshire.

Initially, Oxdale focused on the development and production of one product - the TM400 log splitter. Following the success of the TM400, which remains one of our most popular products selling over 10,000 units nationwide, Oxdale expanded their range and now manufactures more than 14 different models of log splitter. We have also developed a range of grassland management and forestry machinery.

All our machinery is manufactured at the Oxdale factory in Chesterfield, exclusively using British steel. The machinery then goes on to be stocked at a wide range of dealers all over the country. We aim to make our range of products both high quality and affordable, suitable for both the commercial and domestic market.

All oxdale products carry a full 12 month guarentee. (This does not apply to special one off builds or machinery we do not manufacture)

All quotations & orders accepted by Oxdale Products Ltd are subject to the following terms of business:

Orders must be forwarded by email. No responsibility is accepted by Oxdale Products Ltd for goods supplied incorrectly if a written order is not recieved. Credit accounts are to be settled in full by the end of the month following the month of invoice. Overdue accounts will suspended deliveries

We regret that no goods can be returned without authorisation and any such returns will be subject to a handling charge of 10% of the invoiced price. All goods shall remain the property of Oxdale Products Ltd until the customer pays in full. While the goods remain in our ownership, the customer shall keep them and insure them against damage, destruction and theft for their full value and return them to Oxdale Products Ltd on demand.

New equipment is warranted for 12 months. Warranty does not cover mileage or replacement of consumable or wearing parts







Oxdale Products

@oxdaleproducts oxdaleproductsltd

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk

For product demonstrations visit www.oxdaleproducts.co.uk



Contents

FORESTRY	
TM400 PTO400 TM600 PTO600 SE400 RT400	4 5 6 7 8 9
Electric Range TM1000 PTO1000 RT1000 Chippers PTO Saw Bench Electric Saw Bench	10 11 12 13 15-17 18 19
AGRICULTURAL	
Rollers Chain Harrows Weeder Tines Seeder Post Hole Borer Post Knocker Compact Grader Boxes Medium Duty Grader Boxes Heavy Duty Grader Boxes Rotavators Finishing Mowers Flail Mowers Toppers Tipping Trailers Slitter	20-22 23 24-25 26 27 28 29 30 31 32-33 34 35-38 39 40 41
Spring Tine Cultivator Subsoiler Back Hoes Log Grabs Working Platform	42 43 44 45 46



Tractor Mounted Log Splitters







TM400

TM400 Big Base

Axehead

All of our log splitters are designed, built, and tested in the UK. Suitable for tractors which range from the compact models to the higher horsepower machines.

Easy to split logs at waist height and ground level. Fits to a standard rear, three-point linkage but can be adapted to fit a front three-point linkage if required.

For added safety, all hydraulic pipes are covered in anti-burst lagging.

Both hands are required on the lever to operate the ram. The big base model also features an enlarged 700mm working base.

Model	Maximum Log Length	Maximum Ton. Cap.	Cat. Linkage	Min.Oil Flow Rate	Machine Weight	Machine Height
TM400	18"	10	1 & 2	14L/M	64kg	1320mm
TM400 Big Base	18"	10	1 & 2	14L/M	100kg	1320mm



PTO LOG SPLITTERS



PTO400

Our PTO range offers a self-contained hydraulic system which is ideal for older or smaller tractors that have no free-flowing hydraulic system.

Will fit to most tractors where a PTO drive is available.

The PTO400 features a 10 tonne splitting force which is powerful enough to cope with the most demanding of splitting jobs.

For added safety, all the hydraulic pipes are covered in anti-burst laggging and both hands are required on the lever to operate the ram.

The platform is self-cleaning of large logs with a full width of 700mm, available in both standard or big base.

Model	Maximum	Maximum	PTO	Cat.	Machine	Machine
	Log Length	Ton. Cap.	Speed	Linkage	Weight	Height
PT0400	18"	10	320	1 & 2	85kg	1320mm



Tractor Mounted Log Splitters







Head and Spool Block

The TM600 is a high capacity log splitter powerful enough to cope with the most demanding of splitting jobs.

The splitting wedge is specially forged, hardened and has a double chamfer to give the best splitting action available on the market.

For added safety, all the hydraulic pipes are covered in anti-burst lagging and both hands are required on the lever to operate. When the lever is released the ram stops, there is no auto return on our machines. This allows different sized height logs to be split quickly without having to do a full auto return.

Model	Maximum	Maximum	CAT.	Min.Oil	Machine	Machine
	Log Length	Ton. Cap.	Linkage	Flow Rate	Weight	Height
TM600	24"	14	1 & 2	25 L/M	100kg	1550mm



PTO LOG SPLITTERS

PTO600

The PTO600 has been designed to split logs up to 24" in height. It is a self-contained hydraulic system which is ideal for older tractors that have no free-flowing hydraulic system.

Suitable for 35hp tractors and above. Will fit to most tractors where a PTO drive is available.

Larger base allows for easier manoeuvrability of the larger rings of wood.



Model	Maximum Log Length		PTO Speed	CAT. Linkage	Machine Weight	Machine Height
PTO600	24"	14	320	1 & 2	210kg	1550mm



ENGINE DRIVEN LOG SPLITTERS



SE400

The SE400 is an engine driven log splitter powered by a Honda GX200 engine.

This machine is fitted with a Dual speed hydraulic pump which when combined with the unique Oxdale Axe head allows a 10-ton capacity ram to be fitted which makes the splitting operation very quick and efficient.

The log splitter has been designed to be easily wheeled by hand to the location where it is to be used.

Capable of splitting logs up to 18 inch high and is not limited to the width of logs it can split.

The SE400 requires 15litres of ISO 46 hydraulic oil.

Model	Maximum	Maximum	Machine	Machine	Honda
	Log Length	Capacity	Weight	Height	Engine Size
SE400	18"	10T	101kg	1960mm	GX200 6.5hp



ROAD TOWABLE LOG SPLITTERS



The RT400 has all the characteristics of the SE400 with the added benefit of being road towable

The road towable log splitter range can be used either attached or free standing.

Chassis plated, supplied with fully operational lighting board and mudguards. Fully IVA inspected and road legal up to 60mph.

Model	Maximum Log Length	Maximum Capacity	Machine Weight	Machine Height	Honda Engine Size
RT400	18"	10T	175kg	1900mm	GX200 6.5hp



ELECTRIC LOG SPLITTERS



Electric Range

All of our log splitters are designed, built, and tested in Britain.

The electric range features a single-phase electric motor and equipped with a standard household three pin plug.

Dual speed, twin pump technology. Automatically switches over under load to supply maximum speed and splitting performance at all times.

Indoor or outdoor use. Pneumatic wheels for ease of manoeuvrability.



The E400D model features a splitting platform 31" high

Model		Maximum Maximum Log Length Ton. Cap.		Machine Height
E300	12"	10	85kg	1060mm
E400	18"	10	95kg	1320mm
E400D	18"	10	101kg	2010mm

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk



Tractor Mounted Log Splitters



The TM1000 log splitter has been designed for the professional user who splits logs into billets.

This high capacity splitter is for use with medium to large sized tractors and can easily split logs up to a maximum height of 36", no diameter limitations.

The 1000 range has a 16-tonne capacity ram fitted with our unique forged and hardened axe head to give the best splitting action available on the market. For added safety, all our hydraulic pumps are covered in anti-burst lagging and both hands are required on the lever to operate the ram.

Model	Maximum	Maximum	CAT.	Min.Oil	Machine	Machine
	Log Length	Ton. Cap.	Linkage	Flow Rate	Weight	Height
TM1000	36"	16	1 & 2	30 L/M	120kg	2350mm



PTO LOG SPLITTERS



The PTO1000 offers a self-contained hydraulic system which is ideal for older tractors that have no free-flowing hydraulic system. Suitable for tractors of 40hp and above. Will fit to most tractors where a PTO drive is available.

Will take logs up to 36" in length and any diameter. Ideal for splitting logs into billet lengths. Features a 45L hydraulic tank and comes complete with PTO shaft.

Model	Maximum	Maximum	PTO	Cat.	Machine	Machine
	Log Length	Ton. Cap.	Speed	Linkage	Weight	Height
PTO1000	36"	16	320	1 & 2	255kg	2350mm



ROAD TOWABLE LOG SPLITTERS



The road towable log splitter range can be used either attached or free standing.

Chassis plated, supplied with fully operational lighting board and mudguards. Fully IVA inspected and road legal up to 60mph.

It is designed to take logs up to 36" in length and any diameter. Ideal for splitting logs into billet lengths.

Made to special order (please check availability)

Model	Maximum	Maximum	Machine	Machine	Honda
	Log Length	Capacity	Weight	Height	Engine Size
RT1000	36"	16T	310kg	2350mm	GX390 13hp



CUSTOMISING LOG SPLITTERS

Oxdale Products are allso able to provide adapted and custom made log splitters. Your tractor mounted log splitter doesn't need to be ran behind a tractor. We can modify the log splitter so that it can be connected to any machine that has an external hydraulic supply.

E.G - Avant Loaders, Bobcats, Telehandlers (Manitou, JCB, John Deere etc.), Mini Diggers (Dual tracks, Mini 360's etc.).





If this is something you require - please do not hesitate to contact us to discuss your requirements and obtain a quote.



CHIPPERS



Chippers

The Delmorino 3" Chipper is available in a Tractor PTO model or with a Honda GX390 petrol engine.

This bio shredder is both reliable and safe. It surpassed all tests to assure the safety of the operator and came out with top marks for its shredding performance. As it denotes in its name, the Delmorino 3" chipper will chip/shred material up to 3" diameter.

Its gravity fed wide chute allows a wide range of material to easily pass through. The frame is made from high strength steel.

The Delmorino 2" chipper is fitted with a Honda GP200 engine. This bio shredder / chipper is suitable for the semi-professional user.

Like the 3" chipper, the 2" is very safe and reliable and has surpassed all tests to assure the safety of the operator.



CHIPPERS



4.5" Argo Chipper

New for 2021, the Argo is a gravity fed chipper with high level discharge at 1.5m and is 360° adjustable.

It features a high strength, anti-vibration steel frame which is laser cut, machine bent and welded by robot.

It makes use of a V belt transmission with tensioner and comes complete with 2 adjustable counter blades designed to be easily replaceable.

It has a 3-point hitch CAT 1 & 2 and a CAT 4 PTO shaft. It features 4 reversible chipping blades mounted on a ventiliation disc and are easy to replace. The chipper disc has steel bearing supports and is electronically balanced.



SCORPION CHIPPER

A PTO driven professional chipper with high level discharge, it takes logs up to 5" in diameter.

Suitable for tractors 20-60hp.

Features a no-stress system; automatically adjusts the speed of the feed rollers to deal with larger amounts of material and reduce stress on the tractor.

Discharge chute stands 2m high and will rotate 360°.

Comes supplied with a CAT 4 PTO shaft.

Cuts with 4 reversible blades of high resistance steel, mounted on a ventilated disc. Easy access to blade holder for easy maintenance.

Blade holder disc has rotor with steel

bearing supports and is electronically balanced.

Reliability and safety are the key elements of this machine.



Classocietà



PTO SAW BENCHES



The 700mm diameter tungsten tip saw blade provides fast and efficient cutting.

It cuts logs up to 12" in diameter and is fully guarded. It comes equipped with a swinging cradle, emergency stop lever (for effective and safe operation) and a PTO shaft as standard.

We have redesigned the guards to prioritise the safety of the operator.



SAW BENCHES



Electric Saw Bench

The 600mm tungsten tip saw blade is capable of cutting through logs up to 10" in diameter.

It features a single phase electric motor which is designed for safe and effective operation.

A single phase, 16 amp power supply is required to power this saw bench.



ROLLERS



Garden Roller

The garden roller is a smaller, more manageable water ballasted roller. It has a diameter of 16" and comes with a 30mm shaft and greaseable bearings which makes it ideal for smallholdings and gardens.

It can be towed behind a compact tractor or ATV. When empty it is easily manoeuvrable by hand. It is practical to store and is available with a pin or 50mm standard ball hitch.

Width Ft.	Drum Diameter in	Wall Thickness mm	Empty Weight Kg.	Full Weight Kg.	
4	16	5	120	384	
5	16	5	144	464	
6	16	5	185	544	



ROLLERS



The paddock roller is water ballasted which makes it ideal for grassland work. It is fitted with a pin or 50mm standard ball hitch towing point and can be towed by tractor, ATV or 4x4.

It has a 40mm shaft, greaseable bearings and a fully adjustable rear scraper. The roller measures 22" in diameter with 7mm plate steel drums. 3 point linkage available as an optional extra

Width Ft.	Drum Diameter in	Wall Thickness mm	Empty Weight Kg.	Full Weight Kg.
4	22	7	170	500
5	22	7	200	600
6	22	7	252	700
8	22	7	304	800



ROLLERS



Farmland Roller

The farmland roller is water ballasted which makes it ideal for large areas.

It is fitted with an agricultural towing eye and can only be towed behind an agricultural machine.

It has a 2" shaft, greaseable bearings and a fully adjustable scraper


An optional 3-point linkage is also available for this machine

Width ft	Drum Diameter in	Wall Thickness mm	Empty Weight Kg.	Full Weight Kg.	
8	30	10	710	1850	



CHAIN HARROWS







Trailed and Mounted Chain Harrows

Our range of harrows are designed to cover all applications from large farms, small holdings, equestrian venues and sports fields.

Harrowing removes dead thatch lifts vegetation up and levels any mole hills. It allows air movement and root aeration which helps the soil to breathe and improves water infiltration. It reduces disease by exposing fungi and bacteria to sunlight which is essential for the health of the pasture.

All our harrows are designed to pull the tines at the correct angle so that the ground is completely covered.

Size Ft.	Size M.	Trailed	Mounted	3 Way	CAT. Linkage	Tine Thickness
4	1.2	√	~	~	1/2	12mm
6	1.8	✓	~	~	1/2	12mm
8	2.5	√	√	~	1/2	12mm
12	3.6		~		1/2	12mm

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk



GRASSLAND EQUIPMENT

Fixed Weeder Tines

The Oxdale Fixed Weeder grass harrow has revolutionised grass harrowing in recent years, larger working widths, more adjustment and aggressive spring tines mean that a better finish can be achieved faster and at a lower cost.



The fixed weeder comes in widths from a very handy 4ft to a manual folding 12ft, all fitted with 8mm tines. The machines are designed for strength without the need for high horsepower.

The weeder can also be used with the Oxdale Seeder Attachment.

Width	Tines	Rows of Tines	Min. HP	CAT. Linkage
4'	21	3	10	1 & 2
6'	31	3	15	1 & 2
8'	41	3	20	1 & 2



GRASSLAND EQUIPMENT



12FT Folding Weeder Tines

Suitable for tractors of 30hp and above.

Four rows of 8mm tines for optimum ground clearance.

Fold to a width of 4ft (1.2m) making them ideal for narrow gateways and road travel.

Can be used with the seeder attachment.

Width	Tines	Rows of Tines	Min. HP	CAT. Linkage
12' Folding	72	4	30	1 & 2



SEEDER



Seeder Attachment

Can be fitted to all weeder tines or any vehicle with a 12v power supply.

62.3L capacity hopper with stainless steel blades and a 12v motor.

Variable speed control to control spread and consistency

Spread width ranges from 5ft - 45ft.

Stimulates old grass growth to improve yields.

Creates a completely new ley.

Can be ised to spread seed, fertiliser, slug pellets or granular pesticides, herbicides & fungicides.







FENCING EQUIPMENT



Post Hole Borer

Suitable for use with all tractors up to 60hp.

Available with 4", 6", 9" or 12" augers. Spare auger tips and shares also available.

Capable of boring holes up to 3ft/0.9m deep. Maximum PTO input speed of 540rpm. Shear bolt protected.





FENCING EQUIPMENT



Post Knocker

Suitable for use with all tractiors.

60kg (max) weight block which can be reduced by removing leaves. Bolt on side mount brackets are also available should you wish to use the post knocker with a loader or digger.

Requires hydraulic spool connection. Can be used with CAT 1 or 2 linkage.

Equipped with a levelling adjuster and post holding plate.

For larger tractors, Oxdale offers an extension kit (pictured left). This extends the distance between the tractor and post knocker to allow the machine to function with larger tractors.





GRADER BOXES



Compact Grader Boxes

An essential tool for levelling ground. The compact grader is ideal for use on hardcore tracks, spreading soil and rubble.

The tines loosen the material, which is then dragged into the box, dropping out where the ground is lower leaving a level surface.

Width ft	No. of Rippers Legs	No. of Blades	Wall Thickness	Weight kg	CAT Linkage
4	4	2	6mm	120	1
5	5	2	6mm	150	1
6	6	2	6mm	180	1 & 2



GRADER BOXES



Medium Duty Graders

New for 2021. This grader was developed for users with medium HP tractors.

The medium duty grader will stand higher than the standard with 10mm thick steel sides. The back of the machine is made from one piece of sheet metal with added strengthening.

There is a full width box section crossmember with adjustable tines to loosen the surface.

Width ft	No. of Rippers Legs	No. of Blades	Wall Thickness	Weight kg	CAT Linkage
6	6	2	10mm	450	2
8	8	2	10mm	550	2



GRADER BOXES



Heavy Duty Grader Boxes

Heavy duty design. Ideal for use on farm tracks and drives. Durable tines easily break up the ground surface.

Debris is dragged in the box to where the ground is lower where it is deposited. Rear blades level and grade the ground surface.

Width	No. of Ripper Legs	No. of Blades	Wall Thickness	Weight kg	CAT. Linkage
6′	5	2	15mm	690	2
8'	7	2	15mm	890	2
10'	7	2	15mm	1112	2





ROTAVATORS / TILLERS



Del Morino 105 / 125 / 145

The Delmorino Rotavators are an easy to use and a powerful piece of machinery used to carry out all the functions related in various working environments in all types of ground whatever its composition (sandy soil, medium mixture or clay).

The innovative rotor production process is the main guarantee of the quality of our rotary tillers. Everything is taken care of in the smallest details starting from the choice and quality tubes, continuing with the machining of the hub seats performed with a CNC boring machine

The rear baffle (back door) besides preventing any dangerous hurling of stones and other foreign bodies, makes a clod mincing function, the more emphasized the more the baffle is closed.

Model	НР	Cat Link.	СМ	Inches	СМ	Inches	No. of Blades	Kg.
105	12-40	1&2	105	42	120	48	20	166
125	12-40	1&2	125	50	140	56	24	180
145	12-40	1&2	145	58	160	64	28	195

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk





ROTAVATORS / TILLERS



This machine demonstrates Del Morino's experience in both the quality of construction and the final result in the field. It is suitable for the professional farmer working in open fields.

Suitable for heavy work
Universal PTO shaft: CAT 5, with slip clutch
Cast iron gearbox rated up to 70 PTO HP
6 hoes per flange
Chain driven ASA 100 in oil bath with automatic tensioner
Automatic tensioner, adjustable skids
Reinforced 3 point linkage frame

Model	НР	Cat Link.	СМ	Inches	СМ	Inches	No. of Blades	Kg.
186	30-70	2	186	71"	200	80"	40	330

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk





MOWERS



Del Morino Finishing Mower

The Del Morino finishing mower with belt drive is suitable for 12-70hp tractors with CAT1 three-point linkage. The cast iron gearbox delivers 540rm

This mower is supplied with a universal PTO shaft CAT 2. It has three spindles each with single blades for the 120/150/180/215 models.

The machine has rear discharge with an optional mulch system and adjustable height pivoting wheels 20-90mm.

Model	HP	СМ	Inches	СМ	Inches	No. of Blades	Kg.	No. of Belts
120	12-45	120	48	145	58	3	180	2
150	12-70	150	60	160	64	3	212	2
180	12-70	180	72	190	76	3	239	2
215	12-70	215	85	225	90	3	289	2
235	12-70	235	93	245	98	5	320	2





FLAIL MOWERS





106 Standard Headstock

Del Morino Semi Offset Flail Mower

The Del Morino semi offset flail mower is suitable for tractors which are 12-30hp with CAT 1 three-point hitch and manual side shift. It can work close to hedges and under trees. It can be used to cut grass, weeds, and bushes.

The mower is supplied with a universal PTO shaft CAT 2. It has an aluminium gearbox with an integrated free wheel device, 2 belt transmission with an adjustable tensioner, adjustable rear roller 3 position and a rotor with metal spatula flails.

The 106 comes wth a standard headstock.

Model	НР	СМ	Inches	СМ	Inches	No. of Blades	Kg.	No. of Belts
106	12-30	106	42	120	48	16	146	2
132	12-30	132	52	155	62	20	170	2
158	12-30	158	62	180	72	24	196	2





FLAIL MOWERS



Del Morino Heavy Duty Flail Mower

This heavy duty flail mower is suitable for 25-70hp tractors with CAT 1 and 2 three-point hitch. It is supplied with a universal PTO shaft, CAT 4.

It boasts a cast iron gearbox with an integrated free wheel device and pass through shaft, a 3 belt drive system with adjustable tensioner, rotor with heavy duty hammers, adjustable rear roller, adjustable skids and mounting points for a hydraulic side shift.

Model	HP	СМ	Inches	СМ	Inches	No. of Blades	Kg.	No. of Belts
132	15-70	132	50	155	62	20	255	3
158	15-70	158	62	180	72	24	288	3
186	15-70	186	72	205	82	28	324	3
214	15-70	214	85	230	92	32	438	3

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk
For product demonstrations visit www.oxdaleproducts.co.uk





FLAIL MOWERS

Levante Flail Mower

The Levante flail mower is suitable for 80-120hp tractors with CAT 2, 3-point linkage. The gearbox is reversible and has a pass-through shaft.

The mower is supplied with a universal CAT 4 PTO shaft. It produces 540 rpm, has a reinforced, reversible frame for front or rear mounting and a hydraulic side shift. The transmission has 4 heavy duty belts with adjustable tensioner, a rotor with hammer blades, rotor supports and bearings outside of the mulching chamber.

It also comes equipped with a dual shredding blade for extra mulching, adjustable skids and an adjustable rear roller.





Model	HP	Cutting Height CM.	Cutting Height Inches	Cutting Width CM.	Cutting Width Inches	No. of Blades	Kg.	No. of Belts
190	60-120	2-12	1-4	190	75	28	565	4
250	80-120	2-12	1-4	250	98	36	665	4
270	80-120	2-12	1-4	270	106	38	700	4





FLAIL MOWERS


Del Morino Levante Super

New for 2021. The Levante Super has all the characteristics as the Standard Levante. This machine is suitable for heavy duty use on hard and uncultivated soils for the professional user.

Its honeycomb structure with high thickness cover and walls (side walls 10mm) allows the user to cut grasses, bushes, stumble, reeds and even prunings of big diameter saplings - getting good results. For better shredding/cutting and strength, a full width shredding blade is fitted underneath the top of the hood.

It has a hydraulic side shift adjustment which enables the user to not just shift the machine to the left or right but also have optimal control on embankments and slopes. This side shift adjustment makes the machines highly manoeuvrable and can be used as an in-line flail mower behind the tractor, or fully offset to the left, with a cutting angle between -50 and +90 degrees of horizontal. This means that verges, banks, ditches or even the side of low hedges can be maintained with a single machine.









MOWERS



DMK Topper

The DMK range of grass toppers are a strong, simple and efficient way of keeping grass areas neat and tidy with a good performance cut. They are very economic to purchase and maintain.

The machine is connected to the tractor with a 3-point hitch which can be used in an 'off-set position' to make it easier to use under trees and along wall sides.

A shear bolt protection is fitted to the PTO shaft (DMK100 & DMK120) and slip clutch on the DMK180.

The cutting height ranges from 1.2" and 8". A cast iron gearbox rated up to 75hp is fitted as standard which, in turn, has a direct drive to a single rotor with two swinging blades

Model	НР	Working Width	Weight Kg	Cutting Height inch	No. of Blades	RPM
DMK 100	12-80	40	143	1 - 4	2	540
DMK 120	12-80	48	176	1 - 4	2	540
DMK 180	12-80	72	300	1 - 4	2	540

Tel: 01246 529020 Email: sales@oxdaleproducts.co.uk
For product demonstrations visit www.oxdaleproducts.co.uk



TRANSPORT



Tipping Trailer

The Oxdale Tipping Trailer is suitable for use with tractors of 20hp and above. The trailer is a full tipping trailer with 3 stage hydraulic ram fitted with extra crossmembers for added strength in the floor.



The trailers have drop down sides and removable front headboards. Fitted with low profile 23x10.50-12 floatation tyres, suitable for off road use only.

Extension mesh sides and a hydraulic hand pump are also available as optional extras.

Model	Length	Width	Height	Maximum Capacity Weight	Optional Mesh Sides	Drop Sides
OX1500	1840mm	1280mm	1020mm	1.5 tonne	^	~
OX2000	2290mm	1280mm	1020mm	2 tonne	4	4



SLITTER AERATOR



Slitter

The Oxdale Slitter relieves compaction and promotes a healthier root system. It can reduce the need to purchase expensive artificial fertiliser.

Alongside this, the Slitter improves growth and quality of the grass,

It improves drainage whilst simultaneously maximising fertiliser input and eliminating slurry run off.

Range	Width	No. of Blades	Cat. Link	Weight kg	Ballasted Weight kg
Compact	4'	18	1	190	410
Compact	5'	24	1	238	515
Compact	6'	27	1 & 2	285	615
Farmer	8'	36	2	870	1690
Farmer	10'	48	2	1087	2112



CULTIVATION EQUIPMENT



Spring Tine Cultivator

Suitable for use with any tractor.

Easy to adjust and move.

Coulters can be adjusted / removed easily.

Any number or configuration of coulters are available to suit your requirements.

Reversible wear points.



Crumbler Attachment

Crumbler attachment available as an optional extra - POA.

Adjustable height of the crumbler for different levels of cultivation.

Width Ft.	CAT. Linkage	Crumbler	Min. HP	Standard no. of Tines
4	1 & 2	Optional	10	9
6	1 & 2	Optional	15	13
8	1 & 2	Optional	20	18



SUBSOILER/PIPELAYER





Subsoiler / Pipelayer

Suitable for smaller tractors.

Supplied with a pipe and cable laying attachment for fast installation with minimal disruption.

Machine allows for the removal of a compacted soil pan from an area of ground to aid drainage.

Features depth adjustment technology and a reversible point.



ACCESSORIES

Log Grabs

Makes it easier to manoeuvre logs.

Available in two different sizes.

All log grabs are CE marked.



Engine Driven ATV Flail Mower

The engine driven ATV flail mower is available in a 1.2m cutting width. They are driven solely by an electric start, 15hp engine which makes them perfect for use with an ATV. They have wide set tyres for reduced ground compaction and are designed to cut long, overgrown grass.





HANDLING & LOADING

Working Platform

Fits to pallet forks

Safety retaining band behind forks

Work restraint anchorage points

Finger guard mesh back panel

Self closing inward opening gate

Top safety hand rail, intermediate rail and kick plate all around

Non slip chequer plate flooring

Full operating instructions / caution labels



Height	Width	Length	Un l aden Weight	Min. Truck Cap.	Load Centres	Max. Load	Max. Persons
2400mm 94.4"	1250mm 49.2"	1000mm 25.4"	180kg 396.83lb	1.5 tonne	500mm 19.6"	500kg 1102 l b	2

Pallet Fork Mounted Brushes

Fork arm mounted brush enables easy sweeping over large areas.

Durable and long lasting bristles made from polypropylene plastic.

Retains bulk volumes of solid or liquid material.





Units 20-21 Foxwood Road, Chesterfield, Derbyshire, S41 9RF

t. 01246 529 020

e. sales@oxdaleproducts.co.uk

For Northern Ireland and Eire contact:

William Holmes

Warringview, 21 Newline, Waringstown, Co.

Armagh

N. Ireland, BT66 7RY

t. 02838 882 119

m. 07792 658 445

e. wiiliam799@btinternet.com

www.**oxdaleproducts**.co.uk